

Fixed Plugs

Specifications

- Working pressure: 3650 PSI
- 7.8 GPM flow rate
- Maximum temperature: 300°F (149°C)



1/4" fixed quick coupling plugs

Description	Part #
1/4" female x 22 mm x 1.5 mm male	AL454 ¹

¹ For use with AL453 and AL9



Description	Part #
1/4" male x 22 mm x 1.5 mm male	AL455F ²

² For use with AL462 only

3/8" fixed quick coupling plugs



Description	Part #
3/8" female x 22 mm x 1.5 mm male	AL456 ¹

¹ For use with AL453 and AL9



Description	Nickel Plated Brass Part #
3/8" female x 1/2" male plug	AL464 ²

² For use with AL462 only

Sewer Nozzles

Specifications

- Working pressure: 3625 PSI
- Maximum temperature: 300°F (149°C)



Size	Orifice	303 Stainless Steel Part #
3/8"	4.5 mm	SWNZ380-045
	5 mm	SWNZ380-050

Injector Nozzles

Features

- Designed to inject cleaning solutions into high pressure discharge lines
- 3/8" male inlet and outlet

Specification

- Maximum working pressure: 4500 PSI



AL477

Description	Orifice	Flow (GPM)	Part #
adjustable	1.8 mm	2 - 8	AL472
adjustable	2.1 mm	3 - 8	AL477
adjustable	2.3 mm	4 - 8	AL478

Line Strainer

Features

- 3/4" female GHT inlet, 1/2" male NPT outlet
- .60 mesh cuffed filter
- 2 additional 1/4" side ports



Specifications

- Working pressure: 180 PSI
- Maximum flow rate: 8 GPM

Aluminum Part #

AR3000-A2

H