

Dual Lock Quick-Acting Couplings with Ferrule

Features:

- working pressure: **300 PSI** at ambient temperature (70°F)
- for crimp recommendations see page 855
- 3/8" and 1" sizes available upon request, contact Dixon™

Materials:

- plated steel ferrule
- also available in brass and stainless steel




Body Size	Hose ID	Hose OD		Trivalent Chrome Plated Steel	
		From:	To:	Part #	Price/E
1/2"	1/2"	5/4/64"	1-2/64"	PHL8WF	\$42.00
1/2"	3/4"	1-10/64"	1-22/64"	PHL12WF	43.95

F

Dual Lock Quick-Acting Couplings with Knurled Flanged Sleeve

Feature:

- large, raised collar sleeve permits easier handling when wearing gloves



Hose End Barb with Knurled Flanged Sleeve

Body Size	Hose ID Size	Trivalent Chrome Plated Steel		Opt Qty
		Part #	Price/E	
1/2"	3/8"	PHL6FS	\$38.99	25
1/2"	1/2"	PHL8FS	38.99	25
1/2"	3/4"	PHL12FS	40.98	25

Male Pipe Thread with Knurled Flanged Sleeve



Body Size	Male NPT	Part #	Price/E	Opt Qty
1/2"	3/8"	PML6FS	\$37.09	25
1/2"	1/2"	PML8FS	36.91	25
1/2"	3/4"	PML12FS	36.91	25

Female Pipe Thread with Knurled Flanged Sleeve



Body Size	Female NPT	Part #	Price/E	Opt Qty
1/2"	1/2"	PFL8FS	\$41.72	25
1/2"	3/4"	PFL12FS	41.72	25

Dual Y Valves

Features:

- dual action valve, ideal for compressor applications
- pressure rating:
 - non-vented: **600 PSI** WOG
 - vented: **125 PSI** CWP (Cold Working Pressure)



vented

Non-Vented

Female NPT Inlet (1)	Female NPT Outlets (2)	Brass	
		Part #	Price/E
1"	3/4"	BBV100DW	\$167.00
1 1/4"	3/4"	BBV125DW	167.00

Vented

Female NPT Inlet (1)	Female NPT Outlets (2)	Brass	
		Part #	Price/E
1"	3/4"	BBV100DWV	\$167.00
1 1/4"	3/4"	BBV125DWV	167.00