

### P-HV-Series Low Pressure Spring Driven Hose Reel

New

**Features**

- Professional-grade heavy-duty steel construction
- Blue powder coat
- Rolled edges and ribbed discs provide strength and safety
- Hybrid (PVC + rubber) bright yellow hose with a white glossy strip
- Superior visibility, increased hose flexibility, enhanced kink resistance, and reduced coil memory
- 1" solid steel axle and lubricated precision bearings for smooth rotation
- Multi-position lock ratchet mechanism secures hose at desired length
- Enclosed, factory-tuned and matched cartridge-style spring motor
- Made in the U.S.A.

**Materials**

- Solid one-piece, heavy gauge 1/4" steel base and support post
- Non-corrosive stainless-steel spring, pawl, and zinc-plated ratchet

**Specification**

- Maximum temperature 150°F (66°C)



F

With Hose

Hose I.D.	Hose Length	Service	Working Pressure PSI @70°F	Steel Part #
3/8"	50'	air / water	300	PHV3850
1/2"	50'	air / water	300	PHV5050

### SH-HV-Series Low Pressure Spring Driven Hose Reel with Hose

New

**Features**

- Professional-grade heavy-duty steel construction
- Blue powder coat
- Rolled edges and ribbed discs provide strength and safety
- Hybrid (PVC plus rubber) bright yellow hose with a white glossy strip
- Superior visibility, increased hose flexibility, enhanced kink resistance, and reduced coil memory
- Multi-position lock ratchet mechanism secures hose at desired length
- Enclosed factory-tuned and matched cartridge-style spring motor
- Made in the U.S.A.

**Materials**

- Solid one-piece, heavy gauge 1/4" steel base and support post
- Non-corrosive stainless-steel spring, pawl, and zinc-plated ratchet
- 1" solid steel axle and lubricated precision bearings for smooth rotation

**Specification**

- Maximum temperature 150°F (66°C)



With Hose

Hose I.D.	Hose Length	Service	Working Pressure PSI @70°F	Steel Part #
1/2"	50'	air / water	300	SHHV5050