

## Imported Brass Ball Valves

### Application

- For control of air, water, oil, and gas in hose or pipe lines, for other services, please contact Dixon®

### Features

- Blow-out proof stems

### Materials

- PTFE seat, seal and thrust washer
- Chrome-plated brass ball and plated steel handle

### Specifications

- Maximum temperature: **366°F (186°C)**
- Pressure rating: **600 PSI WOG; 150 PSI Working Steam Pressure**

### Approval

- UL listed

### Female NPT x Female NPT



Size	Port	Forged Brass Part #
1/4"	full	FBV25
3/8"		FBV38
1/2"		FBV50
3/4"		FBV75
1"		FBV100
1-1/4"		FBV125
1-1/2"		FBV150
2"		FBV200



### Female NPT x Female NPT



Size	Port	Forged Brass Part #
2-1/2"	full	FBV250
3"		FBV300
4"		FBV400

## Imported Brass Ball Valves with Locking Handle

### Application

- For control of air, water, oil and gas in hose or pipe lines, for other services please contact Dixon®

### Features

- Blow-out proof stem

### Materials

- PTFE seat, seal, and thrust washer
- Chrome-plated brass ball and plated steel handle

### Specifications

- Maximum temperature: **366°F (186°C)**
- Pressure ratings: **600 PSI WOG; 150 PSI working steam pressure**

Female NPT	Port	Forged Brass Part #
1/2"	full	FBVL50
3/4"		FBVL75
1"		FBVL100
1-1/4"		FBVL125
1-1/2"		FBVL150
2"		FBVL200
2-1/2"		FBVL250
3"		FBVL300
4"		FBVL400

