



Dixon Bayco Relief Valve Minimum and Maximum Settings

Pressure and Vacuum relief valves can be factory ordered with a relief setting from within the tables below.

Pressure Relief Valves, Minimum and Maximum Setting

Valve Series	Factory Setting	
	Minimum PSI	Maximum PSI
2180	2	25
A2180	2	27
A2180ADJ ¹	9 ¹	30 ¹
2182	3	24
A2182	6	27
2215 ¹	12 ¹	30 ¹
3180	4	30
A3180	6	32
A3180ADJ ¹	9 ¹	30 ¹

¹ adjustable by a further +/- 3 PSI

- Settings below 9 PSI are obtainable by turning the valve adjustment screw. Example for an 8 PSI setting the valve adjustment would be +4/-2, for 7 PSI +5/-1 and for 6 PSI +6/-0
- Settings above 30 PSI are obtainable by turning the valve adjustment screw. Example for an 31 PSI setting the valve adjustment would be +2/-4, for 32 PSI +1/-5 and for 33 PSI +0/-6

Vacuum Relief Valves, Minimum and Maximum Setting

Valve Series	Factory Setting	
	Minimum Hg	Maximum Hg
1120	6"	24"
2120	5"	24"
3120	11"	25"

Dixon Bayco

800 High Street • Chestertown, MD 21620
phone: 410.778.2000 • fax: 410.778.4702
dixonvalve.com

Dixon Group Canada Ltd.

2315 Bowman Street • Innisfil, Ontario L9S 3V6
ph: 800.355.1991 • fx: 877.436.6251
dixongroupcanada.com